

1、技术参数 Technical Parameters

- ◆ 公称通径 :DN15-DN50
Nominal Diameter: DN15-DN50
- ◆ 公称压力: 6.3MPa
Nominal Pressure: 6.3MPa
- ◆ 适用介质 :R12,R22,R502,R134a,R404a,R507,R717 等制冷剂。
Applicable Medium: R12, R22, R502, R134a, R404a, R507,R717 and other refrigerants.
- ◆ 适用温度: -46℃ ~ +150℃
Applicable Temperature: -46℃ ~ +150℃
- ◆ 结构形式: 角式结构代号 A 直通结构代号 S
Structure Form: Angle Type Structure code is A Straight Type Structure code is S

2、说明 Instruction

TVL 长颈节流阀系列产品, 阀体内部启闭件采用圆锥流线型设计, 有两种不同的方式, TVL-SA 与 TVL-SB, TVL-SA 主要用于膨胀 / 节流管路 (A 型阀芯); TVL-SB 主要用于液体管路的流量调节 (B 型阀芯)。
TVL long-neck regulating valve series, the opening and closing parts inside the valve body adopt a conical streamline design, there are two different types, TVL-SA and TVL-SB, TVL-SA is mainly used for expansion/throttle pipeline (Type A spool); TVL-SB is mainly used for flow regulation of liquid pipelines (type B spool).

3、订货 Order Goods

- ◆ 订货时, 需指定型号、结构形式;
Please tell us the model you want when ordering.
- ◆ 例: TVL - SA 65
E.g.: TVL - SA 65
表示 DN65 长颈节流阀, 结构形式为直通, A 型阀芯
It means DN65 long neck regulating valve, the structure is straight-through, A-type spool



角式 PN63 长颈节流阀 Angle Type PN63 Long Neck Regulating Valve							
型号 Model	通径 Nominal Diameter (DN)	尺寸 Size (mm)					
		ΦD	ΦD1	L	H	H1	H2
TVL-A	15	21.3	15	45	267	223	267
	20	27	20	45	267	223	267
	25	33.7	25	45	267	223	267
	32	38	32	49.5	263	235	277
	40	48.3	38	56	312	282	354
	50	60.3	49	60	292	262	330

直通 PN63 长颈节流阀 Straight Type PN63 Long Neck Regulating Valve							
型号 Model	通径 Nominal Diameter (DN)	尺寸 Size (mm)					
		ΦD	ΦD1	L	H	H1	H2
TVL-S	15	21.3	15	120	245	223	200
	20	27	20	120	245	223	200
	25	33.7	25	120	245	223	200
	32	38	32	128	221	202	210
	40	48.3	38	156	260	239	269
	50	60.3	49	149	260	238	267